

# DEHUMIDIFIERS

## MH Series

MUNDCLIMA®

### Models 20 to 50 L/day

#### Electronic control with various operating modes:

- Continuous Mode
- Preset Mode depending on setting between 35 and 85%
- Comfort Mode (SMD) with automatic humidity adjustment between 45 and 55% depending on the ambient temperature (Model 20 only)
- Adjust air flow (2 speeds)
- WIFI connection (only model 20)
- High-efficiency HEPA filter (Model 20 only)
- Auto-restart and automatic defrost functions
- Timer (24 h)
- Easily removable filters
- Possibility to connect to continuous drain
- Wheels for easy transportation
- Tank with 3 L capacity (Mod. 20 and 30)
- Tank with 6 L capacity (Mod. 50)



MH-20-V10



MH-30-V9  
MH-50-V9

### Model 70 L/day

#### Electronic control with various operating modes:

- Continuous Mode (CO)
- Preset Mode depending on setting between 30 and 90%
- Comfort mode (AU) with automatic humidity adjustment between 50 and 60% depending on the ambient temperature
- Adjust air flow (2 speeds)
- Auto-restart and automatic defrost functions
- Timer (24 h)
- Easily removable filters
- Possibility to connect to continuous drain
- Wheels for easy transport
- Tank with 6,5 L capacity



MH-70-V9

#### TECHNICAL FEATURES:

Model		MH-20-V10	MH-30-V9	MH-50-V9	MH-70-V9	
Code		HU10539	HU10534	HU10535	HU10536	
Power supply	V - Hz	230 - 50	230 - 50	230 - 50	230 - 50	
Absorbed power* / max.	W	360 / 440	550 / 715	850 / 1060	800	
Dehumidification*	litros/día	20	30	50	70	
Air flow rate (High / Low)	m³/h	168 / 99	191 / 166	353 / 319	360 / 280	
Sound pressure level (High)	dB(A)	46	50	50	56	
Dimensions	Width	mm	350	386	392	405
	Height	mm	510	500	616	632
	Deep	mm	245	260	282	268
Weight	kg	14,3	17	19,5	19,3	
Refrigerant	Type/PCA	R 290 / 3	R 290 / 3	R 290 / 3	R 290 / 3	
	Load	kg/TCO <sub>2</sub> eq.	0,07 / 0	0,1 / 0	0,145 / 0	0,153 / 0

\*30°C / 80% HR